

NPS63-80-001

U.

ADA 08194



NAVAL POSTGRADUATE SCHOOL Monterey, California



B

FORMULATION OF EFFICIENT FINITE

ELEMENT PREDICTION MODELS

by

R. T. Williams and A. L. Schoenstadt

January 1980

Technical Report Period: October 1978-December 1979

Approved for public release; distribution unlimited.

Prepared for: Naval Environmental Prediction Research

Facility and Fleet Numerical Oceanographic

Center.

NAVAL POSTGRADUATE SCHOOL Monterey, California 93940

Rear Admiral Tyler F. Dedman Superintendent

J. R. Borsting Provost

The work reported herein was supported by the Naval Environmental Prediction Research Facility and the Fleet Numerical Oceanographic Center.

This report was prepared by:

A. L. Schoenstadt

Associate Professor of Mathematics

RT Williams

R. T. Williams

Professor of Meteorology

Reviewed by:

G. J. Haltiner Chairman

G. J. Haltiner, Chairman Department of Meteorology

Released by:

W. M. Tolles

Dean of Research

Unclassified SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered) READ INSTRUCTIONS REPORT DOCUMENTATION PAGE BEFORE COMPLETING FORM 2. GOVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUTTER NPS63-86-661 TITLE (and Sublitle) Repet for Oct 78 - Dec 79 Formulation of Efficient Finite Element Prediction Models PERFORMING DRG. REPORT NUMBER 8. CONTRACT OR GRANT NUMBER(s) 7. AUTHOR(s) N66856-79-WR-79002 R. T./Williams A. L./Schoenstadt N63134-79-WR-90909 PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940 11. CONTROLLING OFFICE NAME AND ADDRESS Naval Environmental Prediction Research Facility Jan and Fleet Numerical Oceanographic Center NUMBER OF PAGE Monterey, California 93940 15. SECURITY CLASS. (of this report) 14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office) Unclassified 154. DECLASSIFICATION/DOWNGRADING SCHEDULE 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Finite Element Method Numerical Methods Geostrophic Adjustment

ALS RACT (Continue on reverse side if necessary and identify by block number)

This report compares three finite element formulations of the linearized shallow-water equations which are applied to the geostrophic adjustment process. The three corresponding finite difference schemes are also included in the study. The development follows Schoenstadt (1980) wherein the spatially discretized equations are Fourier transformed in x, and then solved with arbitrary initial conditions. The six schemes are also compared by integrating them numerically from an initial state at

DD , TORM, 1473 EDITION OF 1 NOV 65 IS OBSOLETE Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Date

SECURITY CLASSIFICATION OF THIS PAGE WHEN DOLD ENGINE

rest with a height perturbation at a single point. The finite difference and finite element primitive equation schemes with unstaggered grid points give very poor results for the small scale features. The staggered scheme B gives much better results with both finite differences and finite elements. The vorticity-divergence system with unstaggered points also is very good with finite differences and finite elements. It is especially important to take into account these results when formulating efficient finite element prediction models.

V

DD Form 1473 5/N 0102-014-6601

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

ABSTRACT

This report compares three finite element formulations of the linearized shallow-water equations which are applied to the geostrophic adjustment process. The three corresponding finite difference schemes are also included in the study. The development follows Schoenstadt (1980) wherein the spatially discretized equations are Fourier transformed in x, and then solved with arbitrary initial conditions. The six schemes are also compared by integrating them numerically from an initial state at rest with a height perturbation at a single point. The finite difference and finite element primitive equation schemes with unstaggered grid points give very poor results for the small scale features. The staggered scheme B gives much better results with both finite differences and finite elements. The vorticity-divergence system with unstaggered points also is very good with finite differences and finite elements. It is especially important to take into account these results when formulating efficient finite element prediction models.

ACCESSION for	
MTIS	White Section I
DOC	Buff Bootles []
MANNOUNCED	اة
JUSTIFICATION	
81	
DISTRIBUTION/A	VALABILITY CIDES
Dist. AVAIL	and/or SPECIAL
A	

TABLE OF CONTENTS

1.	Introduction 7
2.	Basic Equations 8
3.	Finite Difference and Finite Element Solutions 10
4.	Final State Example14
5.	Conclusions
Refe	erences
Dist	tribution List

 \int_{S}

1. Introduction

.

The finite element method (FEM), which was developed in engineering statics, has recently been introduced into various atmospheric prediction models (Cullen, 1974; Hinsman, 1975; Staniforth and Mitchell, 1977). The FEM is a special case of the Galerkin procedure in which the dependent variables are approximated by a finite sum of spatially varying basis functions with time dependent coefficients. The FEM basis functions are low order polynomials which are zero except in a localized region. The Galerkin procedure produces a set of coupled ordinary differential equations for the coefficients which are solved by introducing finite differences in time (see for example Pinder and Gray (1977)).

FEM models are potentially more accurate than finite difference models, but they normally require more computational effort per degree of freedom. For this reason it is especially important to formulate FEM models efficiently. Kelley and Williams (1976) found considerable small scale noise in an FEM model of the shallow water equations in a channel which had all variables carried at the same nodal points. Winninghoff (1968), Arakawa and Lamb (1977) and Schoenstadt (1980) have demonstrated the advantages of spatial staggering of dependent variables in finite difference models. Also Staniforth and Mitchell (1977, 1978) have obtained excellent results with a vorticity-divergence FEM formulation. This paper will compare these FEM formulations by considering the geostrophic adjustment process with the linearized shallow water equations in one dimension.

2. Basic Equations

The linearized shallow-water equations with no mean flow can be written:

$$\frac{\partial u}{\partial t} - fv + g \frac{\partial h}{\partial x} = 0 , \qquad (2.1)$$

$$\frac{\partial \mathbf{v}}{\partial \mathbf{t}} + \mathbf{f}\mathbf{u} = 0 , \qquad (2.2)$$

$$\frac{\partial h}{\partial r} + H \frac{\partial u}{\partial x} = 0 , \qquad (2.3)$$

where u and v are the perturbation velocities in the x and y directions, respectively, and H and h the mean and perturbed heights of the free surface. Also g represents gravity and f is the coriolis parameter. Note that all quantities are independent of y.

The vorticity and divergence equations are obtained by differentiating (2.1) and (2.2) with respect to x which yields:

$$\frac{\partial D}{\partial t} - f\zeta + g \frac{\partial^2 h}{\partial x^2} = 0 , \qquad (2.4)$$

$$\frac{\partial \zeta}{\partial t} + fD = 0 , \qquad (2.5)$$

$$\frac{\partial h}{\partial t} + HD = 0 , \qquad (2.6)$$

where D = $\partial u/\partial x$ is the divergence and $\zeta = \partial v/\partial x$ is the vorticity. These relations for D and ζ are particularly simple in this case since $\partial u/\partial y = \partial v/\partial y = 0$.

Schoenstadt (1977) solved the continuous equations (2.1)-(2.3) with the of the spatial Fourier transform. If we denote Fourier transforms by a tilde, such as

$$\tilde{u}(k,t) = \int_{-\infty}^{\infty} u(x,t) e^{-ikx} dx, \qquad (2.7)$$

then the set (2.1)-(2.3) can be transformed to the form:

$$\frac{d\tilde{u}}{dt} = \eta f \tilde{v} - i \mu g \tilde{h} , \qquad (2.8)$$

$$\frac{d\tilde{v}}{dt} = -\eta f\tilde{u} , \qquad (2.9)$$

$$\frac{d\tilde{h}}{dt} = -i\mu H\tilde{u} , \qquad (2.10)$$

where η = 1 and μ = k. The quantities η and μ will be useful later when finite difference and finite element solutions are needed. The initial conditions are written

$$\tilde{u}_0 = \tilde{u}(k,0) = \int_{-\infty}^{\infty} u(x,0) e^{-ikx} dx$$
, (2.11)

with similar definitions for \tilde{v}_{o} and \tilde{h}_{o} . Schoenstadt (1977) solved the set (2.7)-(2.9) subject to initial conditions by the eigenvalue-eigenvector approach which gives:

$$\tilde{u}(k,t) = \tilde{u}_{o} \cos vt + \eta f \frac{\tilde{v}_{o}}{v} \sin vt - \frac{i\mu gh_{o}}{v} \sin vt$$
, (2.12)

$$\tilde{\mathbf{v}}(\mathbf{k},t) = -\frac{\eta f}{v} \tilde{\mathbf{u}}_{o} \sin vt + \{\frac{\mu^{2} gH}{v^{2}} + \frac{\eta^{2} f^{2}}{v^{2}} \cos vt\} \tilde{\mathbf{v}}_{o}$$

$$+ \frac{ig\mu\eta f}{v^2} \left\{1 - \cos vt\right\} \tilde{h}_0, \qquad (2.13)$$

$$\tilde{h}(k,t) = -\frac{i\mu H}{v} \tilde{u}_{o} \sin vt - \frac{i\mu \eta f H}{v^{2}} \{1 - \cos vt\} \tilde{v}_{o} + \{\frac{\eta^{2} f^{2}}{v^{2}} + \frac{\mu^{2} g H}{v^{2}} \cos vt\} \tilde{h}_{o}, \qquad (2.14)$$

where:
$$v^2 = \eta^2 f^2 + \mu^2 gH$$
. (2.15)

The transformed vorticity-divergence set (2.4)-(2.6) is written:

$$\frac{dD}{dt} - f\tilde{\zeta} - \mu^2 g\tilde{h} = 0 , \qquad (2.16)$$

$$\frac{d\tilde{\zeta}}{dt} + f\tilde{D} = 0 , \qquad (2.17)$$

$$\frac{d\tilde{h}}{dt} + H\tilde{D} = 0 , \qquad (2.18)$$

where $\mu^2 = k^2$. The solution to this set, which can be obtained directly or by using \tilde{D} = iku and $\tilde{\zeta}$ = ikv in (2.13)-(2.15), is given by:

$$\widetilde{D}(k,t) = \widetilde{D}_{o} \cos vt + \frac{\widetilde{f\zeta}_{o}}{v} \sin vt + \frac{\mu^{2}gh_{o}}{v} \sin vt , \qquad (2.19)$$

$$\tilde{\zeta}(k,t) = -\frac{fD_o}{v} \sin vt + \left[\frac{\mu^2 gH}{v^2} + \frac{f^2}{v^2} \cos vt\right] \tilde{\zeta}_o$$

$$-\frac{\mu^2 f}{v^2} [1 - \cos vt] gh_0, \qquad (2.20)$$

$$\tilde{h}(k,t) = -\frac{H\tilde{D}_o}{v} \sin vt - \frac{Hf}{v^2} [1 - \cos vt] \tilde{\zeta}_o$$

$$+\left[\frac{f^2}{v^2} + \frac{\mu^2 gH}{v^2} \cos vt\right] \tilde{h}_0,$$
 (2.21)

where:

$$v^2 = f^2 + \mu^2 gH . (2.22)$$

3. Finite Difference and Finite Element Solutions

Schoenstadt (1980) carried out a general analysis of the solutions to (2.1)-(2.3) which allowed for spatially centered finite differences or finite elements. We will use the same method to compare certain finite difference and finite element solutions to systems (2.1)-(2.3) and (2.4)-(2.6). The various finite difference and finite element forms corresponding to (2.1)-(2.3) or (2.4)-(2.6) are given in the Appendix. Following Schoenstadt (1980) the Fourier transformed versions of the various numerical schemes for the equations (2.1)-(2.3) can be written in the following form:

$$\alpha(k) \frac{d\tilde{u}}{dt} = f\beta(k) \tilde{v} - ig\sigma(k) \tilde{h}$$
, (3.1)

$$\alpha(k) \frac{d\tilde{v}}{dt} = -f\beta(k) \tilde{u}$$
, (3.2)

$$\alpha(k) \frac{d\tilde{h}}{dt} = -iH\sigma(k) \tilde{u} . \qquad (3.3)$$

The functions $\alpha(k)$, $\beta(k)$ and $\sigma(k)$ are given in Table I for the various schemes considered. This set can be put in the same form as (2.8)-(2.10) by dividing by α and by setting:

$$\eta = \beta/\alpha$$
 and $\mu = \sigma/\alpha$. (3.4)

In this case the frequency is given by

$$v^2 = (\beta^2 f^2 + \sigma^2 g H)/\alpha^2$$
 (3.5)

The solutions to set (3.1)–(3.3) are given by (2.12)–(2.14) with the use of (3.4) and (3.5).

Table I. Coefficients in primitive equations for various numerical schemes.

Scheme differential	α 1	β 1	σ k
A	1	1	sin (k∆x)/∆x
В	1	1	$\sin (k\Delta x/2)/(\Delta x/2)$
FEM A	(2+cos(k∆x))/3	(2+cos(k∆x))/3	sin (k∆x)/∆x
FEM B	(2+cos(k∆x))/3	$(2+\cos(k\Delta x))/3$	$(5\sin(k\Delta x/2)+\sin(3k\Delta x/2))/4\Delta x$

The numerical schemes for the vorticity-divergence system (2.4)-(2.6) lead to the following transformed equations:

$$\alpha \frac{d\tilde{D}}{dt} - \alpha f\tilde{\zeta} - \sigma^2 g\tilde{h} = 0 , \qquad (3.6)$$

$$\alpha \frac{d\tilde{\zeta}}{dt} + f\alpha \tilde{D} = 0 , \qquad (3.7)$$

$$\alpha \frac{d\tilde{h}}{dt} + H\alpha \tilde{D} = 0 , \qquad (3.8)$$

where $\alpha(k)$ and $\sigma(k)$ are given in Table II. This set can be put in the same form as (2.16)-(2.18) by dividing by α and setting:

$$\mu^2 = \sigma^2/\alpha . ag{3.9}$$

The frequency equation (2.22) becomes

$$v^2 = f^2 + (\sigma^2/\alpha)gH$$
, (3.10)

which has a different form from (3.5). The solutions to set (3.6)-(3.8) are given by (3.6)-(3.8) with the use of (3.9) and (3.10).

Table II. Coefficients in vorticity-divergence equations for various numerical schemes.

Scheme α σ^2 Scheme differential 1 κ^2 finite difference 1 $\sin^2(\kappa\Delta x/2)/(\Delta x/2)^2$ FEM $(2+\cos(\kappa\Delta x))/3$ $\sin^2(\kappa\Delta x/2)/(\Delta x/2)^2$

The various parameters which determine the solutions (2.13)-(2.15) and (2.19)-(2.21) are shown in Tables I and II, respectively. Table I contains Schemes A and B for the primitive equations where Scheme A is unstaggered and Scheme B has the velocity points midway between the height points (see Schoenstadt, 1980). The table also includes the finite element forms which are obtained when piecewise linear basis functions are used. Note that k is poorly represented by σ with Scheme A near $k = \pi/\Delta x$, and that the problem remains with the FEM version of Scheme A. The staggered grid gives a much better approximation since spatial derivatives are computed over a distance of Δx compared to $2\Delta x$ with the unstaggered grid.

Table II contains the parameters for the finite difference and finite element versions of the vorticity-divergence set of equations. In this case vorticity, divergence and height are carried at the same points. Note that σ^2 for both cases is the same as the value of σ^2 for Scheme B from Table I. It can be seen from the tables that the staggered primitive equation (Scheme B) and vorticity-divergence formulations have the same values for α and σ and therefore for ν , so that these should give the same solution except for truncation error in the initial conditions.

As pointed out by Schoenstadt (1980), the solutions (2.12)-(2.14) for the various schemes differ only through the coefficients η/ν , μ/ν , and $\eta\mu/\nu^2$, and the same dependence occurs in system (2.19)-(2.21) with $\eta=1$, except that the coefficient $\eta\mu/\nu^2$ does not appear. Figure 1a contains the phase velocity, $c=\nu/k$, as a function of $k\Delta x/\pi$ for the various schemes in Tables I and II as computed from (3.5) and (3.10), respectively. The differential solution approaches f/k for small k and the shallow-water speed (gH) $^{1/2}$ for large k. Scheme A gives the poorest phase speed and the finite element Scheme A is also very poor for the

highest wavenumbers. The finite element scheme B is very close to the differential solution, while the vorticity-divergence FEM scheme is a little higher. The group velocity, $G = dv/d\mu$, is given in Fig. 1b, as a function of $k\Delta x/\pi$. The differential solution is zero at k=0 and it approaches the shallow-water phase speed (gH)^{1/2} for large k. Scheme A and its FEM version are very poor for the short waves since they propagate energy in the wrong direction. In fact the FEM scheme gives a group velocity which is more than double the correct value and of the wrong sign, at certain points. The FEM scheme B gives the best group velocity while the FEM vorticity-divergence scheme gives values that are somewhat higher.

The coefficients η/ν , μ/ν and $\eta\mu/\nu^2$ are given in Fig. 2a, 2b and 2c, respectively, as functions of $k\Delta x/\pi$. Scheme A is the poorest for each coefficient, but the FEM version of scheme A is just as bad for the short waves. The best scheme is the FEM version of scheme B, although the FEM vorticity-divergence scheme is also very good. The coefficient η/ν , which is given in Fig. 2a, is especially important since η^2/ν^2 relates the initial height to the final (steady-state) height field (see (2.14)). In particular, the figure shows that if v_0 = 0, the final h for k = $\pi/\Delta x$ is more than 25 times too large for scheme A and the FEM version of A! This is one reason why non-staggered schemes tend to generate small scale noise. These results were given by Schoenstadt (1980) with the exception of the vorticity-divergence schemes.

4. Final State Example

The two aspects of the geostrophic adjustment process that must be considered in assessing a particular numerical scheme are: 1) forecast time required to reach the adjusted state, 2) the accuracy of the final

adjusted state. The group velocity curves in Fig. 1a provide an indication of the comparative adjustment times for the various schemes. The final adjusted state, which is more important, could be obtained by Fourier transforming the terms that are independent of t in (2.12)-(2.14) or (2.19)-(2.21). However, in this paper the final state will be determined by integrating the finite difference equations in t until the adjusted state is reached. This approach is preferable because time differencing effects are included and a time filter can also be used.

The various sets of equations, which are given in the Appendix are integrated with centered time differences. The time filter developed by Robert (1966) (see also Asselin, 1972) is applied to the past time value with the coefficient γ = .05. The new time values for the FEM schemes are found by Gauss elimination.

The initial conditions are given by:

$$h(x,0) = \begin{cases} a & |x| \le \Delta x/2 \\ 0 & |x| > \Delta x/2 \end{cases}$$
 (4.1)

$$u(x,o) = v(x,o) = 0$$
, or $\zeta(x,o) = D(x,o) = 0$.

These initial conditions are convenient for comparing the various schemes since no truncation error is introduced when the initial vorticity and divergence are computed from these initial velocities. The analytic solution for the final adjusted h field can be obtained by integrating the following expression that was obtained by Schoenstadt (1977):

$$h_{\mathbf{g}}(\mathbf{x}) = h(\mathbf{x},0) - \frac{H}{2\lambda^{2}f} \sum_{\infty}^{\infty} \operatorname{sgn}(\mathbf{x}-\xi) e^{-\left|\mathbf{x}-\xi\right|/\lambda} \left[\frac{g}{f} \frac{\partial h}{\partial \mathbf{x}}(\xi,0) - \mathbf{v}(\xi,0)\right] d\xi ,$$
(4.2)

where $h_S(x)$ is the final adjusted height and $\lambda = (gH)^{1/2}/f$ is the Rossby radius of deformation. The initial geostrophic wind which is required in (4.2) can be conveniently written:

$$\frac{g}{f}\frac{\partial h}{\partial x}(x,0) = \frac{ag}{f}\left[\delta(x+\Delta x/2) - \delta(x-\Delta x/2)\right], \qquad (4.3)$$

where $\delta(x)$ is the delta function.

When (4.1) and (4.3) are introduced into (4.2) the solution becomes:

$$e^{-x/\lambda} \sinh(\Delta x/2\lambda) \qquad \Delta x/2 < x$$

$$h_{s}(x) = a \quad 1 - e^{-\Delta x/2\lambda} \cosh(x/\lambda) \quad -\Delta x/2 \le x \le \Delta x/2 \quad . \quad (4.4)$$

$$e^{x/\lambda} \sinh(\Delta x/2\lambda) \qquad x < -\Delta x/2$$

Fig. 3 contains $h_{\mathbf{g}}(\mathbf{x})$ for the case $\Delta \mathbf{x} = \lambda/2$.

The numerical integrations with the various schemes are performed on a grid of 200 points with cyclic boundary conditions. The initial disturbance at x=0 is placed in the center of the computational domain so that the cyclic boundary conditions will not affect the solution near x=0 until well after the adjusted state is reached. Fig. 3 includes the numerical solutions at t=3 days for the following schemes: A, B and FEM A. Scheme A shows strong oscillations with every other point returning to 0. The FEM scheme A has smaller oscillations near x=0, but they become larger than the oscillations with scheme A farther out. Scheme B gives very smooth behavior and it is close to the analytic solution. The vorticity-divergence system gives the same solution as scheme B, and is very close to the analytic solution as can be seen in Table III which compares the solutions at the first two grid points.

Table III. Numerical solutions h/a at t = 72 hours for the first two grid points for various schemes compared with analytic solution.

x	0	Δx
Differential	0.221	0.153
A	0.459	0.0
В	0.240	0.148
vorticity-divergence	0.240	0.148
FEM A	0.298	0.084
FEM B	0.227	0.157
FEM vorticity-divergence	0.213	0.154

The results given in Fig. 3 and Table III are consistent with the curves for n/ν shown in Fig. 2a, since h_s is proportional to n^2/ν^2 (see (2.14) and (2.21)). In particular the poor behavior for the unstaggered primitive equation schemes (A and FEM A) in Fig. 2a is consistent with the large amplitude short waves in Fig. 3. Also the large oscillations farther out with FEM A may be the result of the large spurious group velocity that is shown in Fig. 1b for that scheme. All the staggered primitive equation and vorticity-divergence schemes give excellent predictions of the final adjusted height field. It should be pointed out that the inclusion of light time smoothing (γ = .05) is necessary to produce the spatially smooth solutions for these cases. Apparently the vanishing group velocity for $k\Delta x/\pi$ = 1 (see Fig. 1b) does not allow the smallest scale gravity waves to propagate out from the initial disturbance. Haltiner and McCollough (1975) demonstrated the usefulness of time filtering in a baroclinic primitive equation model.

5. Conclusions

The objective of this paper is to determine the response of various finite element schemes to small scale initial conditions or small scale forcing. It is especially important that FEM prediction schemes properly describe small scale features, because FEM models usually require more computational effort per degree of freedom than most finite difference models. This study treated the geostrophic adjustment process with the linearized primitive equations and also with the related vorticitydivergence set of equations. The development followed Schoenstadt (1980) wherein the spatially discretized equations were Fourier transformed in x, and then solved with arbitrary initial conditions. These solutions were dependent on certain coefficients which were computed for the various numerical schemes and compared with the differential expressions. Three FEM schemes were examined as well as the three corresponding finite difference schemes. It was found that the unstaggered (scheme A) primitive equation model gives the poorest behavior followed by the corresponding FEM formulation. These schemes are especially bad for the shortest resolvable scales. The finite difference primitive equation model, which staggers height points between velocity points (scheme B) has much better behavior than the unstaggered schemes. The vorticity-divergence model where G. D and h are carried at the same points has the same coefficients as scheme B. The FEM version of scheme B, which has staggered nodal points. was found to have the best behavior and the FEM vorticity-divergence model was also found to be very good.

The six schemes were also compared by integrating them numerically with centered time differences from an initial state at rest with a height perturbation at a single point. The analytic solution for this initial

state approached a smooth height field after the inertial gravity waves radiated away. Scheme A and the FEM form of scheme A gave very poor solutions with large oscillations from point to point. All of the other schemes produced smooth solutions with the FEM schemes being the most accurate. The smoothness of these solutions was improved by light time smoothing. Although the initial state used in this comparison is somewhat extreme, it shows clearly the superiority of the staggered primitive equation and vorticity-divergence schemes over the non-staggered primitive equation schemes.

Winninghoff (1968), Arakawa and Lamb (1977) and Schoenstadt (1980) have demonstrated the advantages of spatial staggering of predictive variables in finite difference models. Our results strongly indicate that FEM models should either use staggered nodal points in the primitive equations or unstaggered nodal points in the vorticity-divergence equations (see also Schoenstadt, 1980). In fact Staniforth and Mitchell (1977, 1978) have developed a FEM model based on the vorticity-divergence form of the shallow-water equations that produces smooth forecasts with only time smoothing. In contrast, Kelley and Williams (1976) obtained very noisy results with an unstaggered FEM model which used the primitive equations for flow in a channel. If non-staggered finite FEM element models are used, it is often necessary to use high order smoothing to damp the small scales as discussed by Cullen (1976). Thacker (1978) tested a finite element formulation of the linearized shallow-water equations with staggered nodal points and he obtained smooth solutions.

さいて まましまりこう

Since FEM models usually require more computer time per degree of freedom, it is very important for the numerical scheme used to be accurate for as small a scale as possible. In this paper we have shown that the

poor geostrophic adjustment for small scale initial conditions. The same conclusion follows for small scale heating. On the other hand either the use of the primitive equations with staggered nodal points or the vorticity-divergence equations with unstaggered nodal points gives excellent treatment of small scale features in the geostrophic adjustment process. Clearly, the use of either formulation should be much more efficient than the unstaggered primitive equations, even when the latter have smoothing to destroy the smallest scale features.

REFERENCES

- Arakawa, A. and V. Lamb, 1977: Computational design of the basic dynamical processes of the UCLA General Circulation Model. Methods of Computational Physics, Academic Press, 17, 174-266.
- Asselin, R., 1972: Frequency filter for time interpolations. Mon. Wea. Rev., 100, 487-490.
- Cullen, M.J.P., 1974: Integration of the primitive equations on a sphere using the finite element method. Quart. J. R. Met. Soc., 100, 555-562.
- , 1976: On the use of artificial smoothing in Galerkin and finite difference solutions of the primitive equations. Quart. J. R. Met. Soc., 102, 77-93.
- Haltiner, G. J. and J. McCollough, 1975: Experiments in the initialization of a global primitive equation model. <u>J. Appl. Meteor.</u>, <u>14</u>, 281-288.
- _____, and R. T. Williams, 1980: <u>Numerical Prediction and Dynamic Meteo-rology</u>. John Wiley and Sons, Inc.
- Hinsman, D. E., 1975: Application of a Finite Element Method to the Barotropic Primitive Equations. M.S. Thesis, Naval Postgraduate School, Monterey, California, 116 pp.
- Kelley, R. G. and R. T. Williams, 1976: A Finite Element Prediction Model with Variable Element Sizes. Naval Postgraduate School Report, NPS-63Wu76101, 109 pp.
- Pinder, G. F. and W. G. Gray, 1977: Finite Element Simulation in Surface and Subsurface Hydrology. Academic Press, New York, 295 pp.
- Robert, A., 1966: The integration of a low order spectral form of the primitive meteorological equations. J. Meteor. Soc. Japan, 44, 237-245.
- Schoenstadt, A., 1977: The effect of spatial discretization on the steady-state and transient behavior of a dispersive wave equation. J. Comp. Phys., 23, 364-379.
- _____, 1980: A transfer function analysis of numerical schemes used to simulate geostrophic adjustment. Mon. Wea. Rev., 108.
- Staniforth, A. N., and H. L. Mitchell, 1977: A semi-implicit finiteelement barotropic model. Mon. Wea. Rev., 105, 154-169.
- ______, 1978: A variable-resolution finite-element technique for regional forecasting with the primitive equations. Mon. Wea. Rev., 106, 439-447.

- Thacker, W. C., 1978: Comparison of finite-element and finite-difference schemes. Part I: One-dimensional gravity wave motion. J. Phys. Oceanogr., 8, 676-679.
- Winninghoff, F., 1968: On the Adjustment Toward a Geostrophic Balance in a Simple Primitive Equation Model with Application to the Problem on Initialization and Objective Analysis. Doctoral Dissertation, UCLA, pp 161.

Appendix

In this Appendix the spatially discretized prediction equations are given for each scheme with $x = m\Delta x$. The following schemes approximate the primitive equations (2.1)-(2.3):

Scheme A

$$\frac{\partial u_m}{\partial t} - fv_m + \frac{g(h_{m+1} - h_{m-1})}{2\Delta x} = 0 ,$$

$$\frac{\partial v_m}{\partial t} + fu_m = 0 ,$$

$$\frac{\partial h_m}{\partial t} + H \left(\frac{u_{m+1} - u_{m-1}}{2\Delta x} \right) = 0.$$

FEM Scheme A

$$M \frac{\partial u_{m}}{\partial t} - f Mv_{m} + \frac{g(h_{m+1} - h_{m-1})}{2\Delta x} = 0 ,$$

$$M \frac{\partial v_{m}}{\partial t} + f Mu_{m} = 0 ,$$

$$M \frac{\partial u_{m}}{\partial t} + H (\frac{u_{m+1} - u_{m-1}}{2\Delta x}) = 0 .$$

Scheme B

$$\frac{\partial u_{m}}{\partial t} - fv_{m} + \frac{g(h_{m+1/2} - h_{m-1/2})}{\Delta x} = 0,$$

$$\frac{\partial v_{m}}{\partial t} + fu_{m} = 0,$$

$$\frac{\partial h_{m}}{\partial t} + H(\frac{u_{m+1/2} - u_{m-1/2}}{\Delta x}) = 0.$$

FEM Scheme B

$$\begin{split} & \text{M} \, \frac{\partial u_{\text{m}}}{\partial t} - \, f \text{M} v_{\text{m}} + \frac{5}{8} (\frac{^{\text{h}}_{\text{m}} + 1/2 - ^{\text{h}}_{\text{m}} - 1/2}{\Delta x}) \, + \frac{3}{16} (\frac{^{\text{h}}_{\text{m}} + 1/2 - ^{\text{h}}_{\text{m}} - 1/2}{\Delta x}) \, = \, 0 \, , \\ & \text{M} \, \frac{\partial v_{\text{m}}}{\partial t} + \, f \text{M} u_{\text{m}} \, = \, 0 \, , \\ & \text{M} \, \frac{\partial h_{\text{m}}}{\partial t} + \, H [\frac{5}{8} \, (\frac{^{\text{u}}_{\text{m}} + 1/2 - ^{\text{u}}_{\text{m}} - 1/2}{\Delta x}) \, + \frac{3}{8} \, (\frac{^{\text{u}}_{\text{m}} + 3/2 - ^{\text{u}}_{\text{m}} - 3/2}{\Delta x}) \, = \, 0 \, , \end{split}$$

where $M^{\alpha}_{m} = (\alpha_{m+1} + 4\alpha_{m} + \alpha_{m-1})/6$.

Scheme B is staggered in such a way that the height points are equi-distant between the velocity points. The FEM equations can be derived with piecewise linear basis functions (see for example Chapter 6 in Haltiner and Williams, 1980).

The vorticity-divergence system (2.4)-(2.6) is approximated with the following schemes.

Vorticity-Divergence

$$\frac{\partial D_{m}}{\partial t} - f\zeta_{m} + g \left(\frac{h_{m+1} - 2h_{m} + h_{m-1}}{\Delta x^{2}} \right) = 0 ,$$

$$\frac{\partial \zeta_{m}}{\partial t} + fD_{m} = 0 ,$$

$$\frac{\partial h_{m}}{\partial t} + HD_{m} = 0 .$$

Finite Element Vorticity-Divergence


$$M \frac{\partial D_{m}}{\partial t} - fM\zeta_{m} + g \frac{h_{m+1} - 2h_{m} + h_{m-1}}{\Delta x^{2}} = 0 ,$$

$$M \frac{\partial \zeta_{m}}{\partial t} + fMD_{m} = 0 ,$$


$$M \frac{\partial h_{m}}{\partial t} + HMD_{m} = 0 .$$

Figure Captions

- The phase velocity c = ν/μ, and the group velocity G = dν/dμ as functions of kΔx/π for various numerical schemes. The curves are labeled as follows: 1) differential solution, 2) scheme A, 3) scheme B and vorticity divergence finite difference scheme, 4) FEM scheme A, 5) FEM scheme B, 6) FEM vorticity-divergence scheme. These results use the following values: gH = 10 m²s⁻², f = 10⁻⁴s⁻¹, Δx = 500 km.
- Fig. 2. The coefficients η/ν , μ/ν and $\eta\mu/\nu^2$ as functions of $k\Delta x/\pi$, with the same labeling as in Fig. 1.
- Fig. 3. The numerical solutions for schemes A, B and FEM A as functions of $x/\Delta x$ at t=3 days. The steady-state differential solution, which is given by (4.4), is included for comparison.



IGURE 1.






FIGURE 2.




FIGURE 3.

DISTRIBUTION LIST

		No.	Copie
1,	Defense Technical Information Center Cameron Station Alexandria, Virginia 22314		2
2.	Library, Code 0142 Naval Postgraduate School Monterey, California 93940		2
3.	Dr. R. T. Williams, Code 63Wu Department of Meteorology Naval Postgraduate School Monterey, California 93940	•	15
4.	Air Force Geophysics Laboratory Exchange Library Sulls Stop 29 Hanscom AFB Bedford, Massachusetts 01730		1
5.	Commander, Air Weather Service Military Airlift Command United States Air Force Scott Air Force Base, Illinois 62226		1
6.	Dr. A. Arakawa Department of Meteorology University of California Los Angeles, California 90024		1
7.	Dr. David A. Archer Douglas DuPont Rachford, Inc. 6150 Chevy Chase Houston, Texas 77027		1
8.	Atmospheric Sciences Library National Oceanic and Atmospheric Administration Silver Spring, Maryland 20910		1
9.	Dr. E. Barker Naval Environmental Prediction Research Facility Monterey, California 93940		1
10.	Dr. Tom Beer Western Australian Institute of Technology Hayman Road South Bentley Western Australia 6102		1
11.	Dr. W. Blumen Department of Astro-Geophysics University of Colorado Boulder, Colorado 80302		1

12.	Dr. F. P. Bretherton National Center for Atmospheric Research P.O. Box 3000 Boulder, Colorado 80303	1
13.	Prof. Dr. Jurgen Brickmann Universitat Konstanz, Fachbereich Chemie 775 Konstanz Postfach 77 33, West Germany	1
14.	Dr. John Brown National Meteorological Center/NOAA World Weather Building Washington, D.C. 20233	1
15.	Dr. CP. Chang, Code 63Cp Department of Meteorology Naval Postgraduate School Monterey, California 93940	1
16.	Prof. J. G. Charney 54-1424 Massachusetts Institute of Technology Cambridge, Massachusetts 02139	1
17.	Dr. M.J.P. Cullen Meteorological Office Bracknell, Berks, United Kingdom	1
18.	Dean of Research, Code 012 Naval Postgraduate School Monterey, California 93940	2
19.	Dr. Tom Delmer Sciences Applications, Inc. P.O. Box 2351 La Jolla, California 92037	1
20.	Department of Oceanography, Code 68 Naval Postgraduate School Monterey, California 93940	1
21.	Dr. D. Dietrick JAYCOR 205 S. Whiting St., Suite 409 Alexandria, Virginia 22304	1
22.	Dr. Hugh W. Ellsaesser Lawrence Livermore Laboratory P.O. Box 808 Livermore, California 94550	1

23.	Dr. R. L. Elsberry, Code 63Es Department of Meteorology Naval Postgraduate School Monterey, California 93940	1
24.	Prof. F. D. Faulkner, Code 53Fa Department of Mathematics Naval Postgraduate School Monterey, California 93940	1
25.	Commanding Officer Fleet Numerical Oceanographic Center Monterey, California 93940	10
26.	Dr. Richard Franke, Code 53Fe Department of Mathematics Naval Postgraduate School Monterey, California 93940	1
27.	Dr. J. A. Galt NOAA - Pac Mar Envir Lab University of Washington Seattle, Washington 98105	1
28.	Dr. W. L. Gates Department of Meteorology Oregon State University Corvallis, Oregon 97331	1
29.	Dr. Ian Gladwell Department of Mathematics University of Manchester Manchester M13 9PL, England United Kingdom	1
30.	Dr. Earl Gossard Wave Propagation Laboratory NOAA/ERL Boulder, Colorado 80302	1
31.	Dr. G. J. Haltiner, Code 63Ha Chairman, Department of Meteorology Naval Postgraduate School Monterey, California 93940	1
32.	Dr. R. L. Haney, Code 63Hy Department of Meteorology Naval Postgraduate School Monterey, California 93940	1
33.	Captain John L. Hayes Air Force Global Weather Central PSC #2, Box 7141 Offutt AFB, Nebraska 68113	1

34.	Dr. J. C. Heinrich Case Western Reserve University Department of Early Sciences Cleveland, Ohio 44106	1
35.	Dr. D. Narayana Holla Department of Mathematics Indian Institute of Technology, Bombay P.O., I.I.T. Bombay Powai, Bombay 400 076, India	1
36.	Dr. J. Holton Department of Atmospheric Sciences University of Washington Seattle, Washington 98105	1
37.	Dr. W. Horsthemke Universite Libre De Bruxelles-Faculte Des Sci. Service De Chimie Physique II-Prof. Prigogine C.P. 231 Campus Plaine-Bd. du Triomphe 1050 Bruxelles, Belgium	1
38.	Dr. B. J. Hoskins Department of Geophysics University of Reading Reading, United Kingdom	1
39.	Dr. D. Houghton Department of Meteorology University of Wisconsin Madison, Wisconsin 53706	1
40.	Dr. Dennis C. Jespersen Department of Mathematics Oregon State University Corvallis, Oregon 97331	1
41.	Dr. E. J. Kansh U.S. Department of the Interior Bureau of Mines Pittsburgh, Pennsylvania 15213	1
42.	Dr. S. K. Kao Department of Meteorology University of Utah Salt Lake City, Utah 84112	1
43.	Dr. A. Kasahara National Center for Atmospheric Research P.O. Box 3000 Boulder, Colorado 80303	1

44.	Dr. L. D. Kovach, Code 53Kv Department of Mathematics Naval Postgraduate School Monterey, California 93940	1
45.	Dr. Ing. J. Kumicak Institute of Radioecology and Applied Nuclear Techniques Komenskeho 9, P.O. Box A-41 040 61 Kosice, CSSR Czechoslovakia	1
46.	Dr. Robert L. Lee Atmospheric and Geophysical Sciences Division University of California P.O. Box 808 Livermore, California 94550	2
47.	Dr. C. E. Leith National Center for Atmospheric Research P.O. Box 3000 Boulder, Colorado 80303	1
48.	Dr. J. M. Lewis Laboratory for Atmospheric Research University of Illinois Urbana, Illinois 61801	1
49.	Dr. Mei-Kao Liu System Applications, Inc. 950 Northgate Drive San Rafael, California 94903	1
50.	Dr. E. N. Lorenz Department of Meteorology Massachusetts Institute of Technology Cambridge, Massachusetts 02139	1
51.	Lieutenant Olaf M. Lubeck COMNAVMARIANAS, Box 12 FPO San Francisco 96630	1
52.	Dr. F. Ludwikow Medical School Department of Biophysics ul. Chalubinskiego 10, 50-368 Wroclaw, Poland	1
53.	Dr. Leon Lupidus Princeton University School of Engineering/Applied Science The Engineering Quadrangle Princeton New Jersey 08540	1

54.	Dr. R. Madala, Code 6780 Naval Research Laboratories Washington, D.C. 20375	1
55.	Dr. J. D. Mahlman Geophysical Fluid Dynamics Laboratory Princeton University Princeton, New Jersey 08540	1
56.	Dr. Alsan Meric Applied Mathematics Division Marmara Research Institute P.K. 141, Kadikoy Istanbul, Turkey	1
57.	Meteorology Library, Code 63 Naval Postgraduate School Monterey, California 93940	1
58.	Dr. G. Morris, Code 53Mj Department of Mathematics Naval Postgraduate School Monterey, California 93940	1
59.	Prof. J. L. Morris Computer Science University of Waterloo Waterloo, Ontario, Canada	1
60.	National Center for Atmospheric Research P.O. Box 1470 Boulder, Colorado 80302	1
61.	Officer in Charge Naval Environmental Prediction Research Facility Monterey, California 93940	10
62.	Naval Oceanographic Office Library, Code 3330 Washington, D.C. 20373	1
63.	Commander Naval Oceanography Command National Space Technology Laboratories Bay St Louis, Mississippi 39520	1
64.	Director, Naval Research Laboratory Attn: Technical Services Information Center Washington, D.C. 20390	1
65.	Office of Naval Research Department of the Navy Washington, D.C. 20360	1

00.	Laboratory for Atmospheric Research University of Illinois Urbana, Illinois 61801	
67.	Prof. K. Ooyama National Center for Atmospheric Research P.O. Box 3000 Boulder, Colorado 80303	•
68.	Dr. I. Orlanski Geophysical Fluid Dynamics Laboratory Princeton University Princeton, New Jersey 08540	•
69.	Prof. H. D. Orville Institute of Atmospheric Sciences South Dakota School of Mines and Technolgoy Rapid City, South Dakota 57701	•
70.	Dr. Darrell W. Pepper Environ. Transport Division E. I. du Pont de Nemours & Co., Inc. Savannah River Laboratory Aiken, South Carolina 29801	•
71.	Prof. N. A. Phillips National Meteorological Center/NOAA World Weather Building Washington, D.C. 20233	•
72.	Dr. S. Piacsek NORDA 320 NSTL Station, Mississippi 39529	•
73.	Dr. A. P. Raiche Minerals Reserach Laboratories, CSIRO P.O. Box 136 North Ryde, NSW 2113, Australia	•
74.	Dr. T. Rosmond Naval Environmental Prediction Research Facility Monterey, California 93940	3
75.	Prof. D. Salinas, Code 69Zc Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93940	•
76.	Dr. Y. Sasaki Department of Meteorology University of Oklahoma Norman, Oklahoma 73069	

77.	Department of Mathematics Naval Postgraduate School Monterey, California 93940	10
78.	Prof. R.C.J. Somerville Head, Climate Research Group, A-024 Scripps Institution of Oceanography University of California, San Diego La Jolla, California 92093	1
79.	Dr. Fred Shuman, Director National Meteorological Center World Weather Building Washington, D.C. 20233	1
80.	Dr. J. Smagorinsky, Director Geophysical Fluid Dynamics Laboratory Princeton University Princeton, New Jersey 08540	1
81.	Dr. Andrew Staniforth Recherce en Prevision Numerique West Isle Office Tower, 5 ieme etage 2121 route Trans-Canada Dorval, Quebec H9P1J3, Canada	1
82.	Dr. Mevlut Teymur Applied Mathematics Division Marmara Research Institute P.K. 141, Kadikoy Istanbul, Turkey	1
83.	Dr. W. C. Thacker National Oceanic and Atmospheric Administration 15 Rickenbacker Causeway Miami, Florida 33149	1
84.	Prof. Carroll O. Wilde, Code 53Wm Chairman, Department of Mathematics Naval Postgraduate School Monterey, California 93940	1
85.	Dr. D. Williamson National Center for Atmospheric Research P.O. Box 3000 Boulder, Colorado 80303	1
86.	Dr. F. J. Winninghoff 3101 Ocean Park Blvd Sta 101 Santa Monica, California 90405	1

87.	Dr. M. G. Wurtele	1
	Department of Meteorology	
	University of California	
	Los Angeles, California 90024	
88.	Dr. J. Young	1
	Department of Meteorology	•
	University of Wisconsin	
	Madison, Wisconsin 53706	
89.	Prof. O. C. Zienkiewicz, Code 69Zw	1
	Department of Mechanical Engineering	
	Naval Postgraduate School	
	Monterey, California 93940	
	* * ·	